



IQ^{V20} Impactool™
W5132 3/8" & W5152 1/2"



REAL TOOLS FOR REAL WORK.™

CORDLESS. POWERFULL.

Ingersoll Rand W5132 3/8" IQ^{V20} Impactool™

Introducing the Ingersoll Rand W5132. The first 3/8" cordless impactool that delivers the power of air. Built on our 100 year reputation, this tool offers the power you want with the control that you need.



Vehicle Repair



Tire Changing



Fleet Truck Maintenance



Industrial & MRO

Tool Features

POWER

With 50% more torque than the leading 3/8" cordless impactool, our powerful brushless motor and impact mechanism are finely tuned to unleash best in class power-to-weight ratio with 550 ft-lbs of nut-busting torque and 365 ft-lbs of MAX torque at barely 5.1 lbs.

CONTROL

The IQ^V Power Control System includes 4 modes: Max Power, Mid Power, Wrench Tight, and Hand Tight. From brake calipers to valve covers and everything in between, there's no need to switch tools. With an easy dial right on the tool, the W5132 delivers just the right amount of torque when you need it.

DURABILITY

Protected by a patented steel reinforced frame and impact-and-chemical resistant housing, the W5132 is built to last. The IQ^V brushless motor technology delivers more power and efficiency providing you with a longer life motor you can rely on.

ACCESS

At 6.5", the short tip-to-tail design and all-new shadowless task light provide increased visibility and access no matter where your work may be hiding.



| MODE | HAND TIGHT | WRENCH TIGHT | MID POWER | MAX POWER |
|------------|------------|---------------|-----------------|-----------------|
| ft-lb (Nm) | 2-9 (3-12) | 10-24 (13-33) | 25-240 (34-325) | 25-340 (34-460) |
| | 365 (500) | 365 (500) | 365 (500) | 365 (500) |
| RPM | 0-800 | 0-1600 | 0-2100 | 0-2100 |
| BOLT SIZE | M6-M14 | M8-M14 | M14-M22 | M14-M22 |
| SHUT OFF | ✓ | ✓ | | |



*Estimated torque values

Specs

| IQ ^{V20} Series™ W5132 & W5152 Cordless Impactools™ | | | | | | Tool & Battery | |
|--|---------|------------|-----------------------|-------------------------|---------------------------------|----------------|-----------------|
| Model | Battery | Voltage DC | Drive Size, Type | MAX Torque ft.-lb. (Nm) | Nut-Busting Torque ft.-lb. (Nm) | Weight lb (kg) | Length in. (mm) |
| W5132 | BL2022 | 20 | 3/8", Square Hog Ring | 365 (495) | 550 (745) | 5.13 (2.33) | 6.54 (166) |
| W5132 | BL2012 | 20 | 3/8", Square Hog Ring | 295 (400) | 400 (540) | 4.48 (2.04) | 6.54 (166) |
| W5152 | BL2022 | 20 | 1/2", Square Hog Ring | 365 (495) | 550 (745) | 5.15 (2.34) | 6.68 (170) |
| W5152 | BL2012 | 20 | 1/2", Square Hog Ring | 295 (400) | 400 (540) | 4.5 (2.05) | 6.68 (170) |



W5152-K22

The W5132 & W5152 are also available in kits.

| Item No. | Kit Details |
|-----------|--|
| W5132-K12 | 1 BL2022 Battery, Tool, Charger, Bag |
| W5132-K22 | 1 BL2012 Battery, 1 BL2022 Battery, Tool, Charger, Bag |
| W5152-K12 | 1 BL2022 Battery, Tool, Charger, Bag |
| W5152-K22 | 1 BL2012 Battery, 1 BL2022 Battery, Tool, Charger, Bag |

IQ^VSeries WARRANTY

IQ^V Series Includes IQ^{V20} and IQ^{V15}

3 Year

Limited
Warranty on
Tools and
Chargers

2 Year

High-Capacity
Battery
Replacement

1 Year

Tool, Battery & Charger
Replacement

See IngersollRand.com/ForMore for official Terms & Conditions. May vary by country.



Ingersoll Rand (NYSE:IR) advances the quality of life by creating and sustaining comfortable and efficient environments. Our people and our family of brands — including Club Car®, Ingersoll Rand®, Thermo King® and Trane® — work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$12 billion global business committed to a world of sustainable progress and enduring results.